



## TEXAS TEXMARINE 60

High Performance System Oil

# PRODUCT DATA SHEET

Issue on 14 April 2017

Texas Petrochemical Asia Pacific Pte Ltd

Singapore 629170

Tel: 65-6262 6538

Fax: 65-6262 6537

Website: [www.texaslub.com](http://www.texaslub.com)

### DESCRIPTION

**TEXAS TEXMARINE 60** is a high performance oil low speed diesel engines lubricant. It is a blend of highly refined high viscosity index base oil and a balanced selection of additives allowing it to provide the highest levels of machinery protection in highly rated low speed marine engine and it can also be used in many different marine equipment.

### PERFORMANCE STANDARDS

- API CF

### MAIN APPLICATION

- Crankcase systems of low-speed, crosshead, marine diesel engines
- Main and Auxiliary Trunk Piston diesel engines burning distillate fuels
- Ancillary Equipment

### BENEFITS

- Effective neutralizes highly corrosive combustion acids
- High dispersion level that keeps crankcases clean and optimize efficiency
- Excellent resistance to the oxidation degradation.
- Good TBN retention.
- Exceptional detergency level.
- Anti-corrosion, anti-rust and anti-wear properties.
- Good air release & anti-foam properties.

### TYPICAL PROPERTIES

TEXMARINE 60	SAE 30	SAE 40
Density, kg/Litre @ 15°C	0.895	0.898
Kinematic Viscosity, mm <sup>2</sup> /s @ 40°C	109	143
Kinematic Viscosity, mm <sup>2</sup> /s @ 100°C	11.9	14.3
Viscosity Index	97	97
Pour Point, °C	-6	-6
Flash Point COC, °C	220	220
TBN	6	6